

Confidential Report

Our Ref: 23/62154E/06/24







Client:

Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 21 June 2024

Our Ref: 23/62154E/06/24 Your Ref: 1017879

Page: 1 of 3

Vita Cellular Foams (UK) Limited

Oldham Road Middleton Manchester M24 2DB

Job Title: Fire Test on One Foam Sample

Clients Order Ref: 1017879

Date of Receipt: 14 June 2024

Date Test Started: 21 June 2024

Description of Sample: One sample of foam, which was referenced by the client as;

OB33 160, ref-241023

Work Requested: We were asked to make the following fire test:

Schedule 1 Part 1 of the Furniture and Furnishings (Fire) (Safety) Regulations 1988, Ignitability test for foam.

* subcontracted test, UKAS accredited

** subcontracted test, EN ISO/IEC 17025 accredited

*** not UKAS accredited





Note: This report relates only to the items tested.



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 21 June 2024

Our Ref: 23/62154E/06/24 Your Ref: 1017879

> Page: 2 of 3

Client: Vita Cellular Foams (UK) Limited

Schedule 1 Part 1 of the Furniture and Furnishings (Fire) (Safety) Regulations 1988 S.I. No. 1324 (as amended by SI 1989 No. 2358, SI 1993 No. 207 & SI 2010 No. 2205), Ignitability test for foam.

Conditioning

All materials used were conditioned in the environments specified in Clause 5 of BS 5852: 1990 Methods of test for the ignitability of upholstered composites for seating by flaming sources.

Testing

The material was tested according to BS 5852: Part 2: 1982. Methods of test for the ignitability of upholstered composites for seating by flaming sources against Ignition Source 5 under a cover fabric corresponding to the standard FR polyester woven fabric specified in the above regulations.

It should be noted that the results of BS 5852: Part 2: 1982 relate only to the ignitability of the combination of materials under test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Results

Specimen No.	1	2
Initial mass of assembly (g)	6338	6337
Final Mass of assembly (g)	6309	6303
Mass loss (g)	29	34
Flaming Duration (mins/secs	3.19	3.37
Smouldering Duration (mins/secs)	5.12	5.59

Criteria: mass loss is less than 60g.

> flaming duration is less than 10 mins smouldering duration is less than 60 mins





1066



Wira House, West Park Ring Road, Leeds, LS16 6QL, UK.

Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 21 June 2024

Our Ref: 23/62154E/06/24 Your Ref: 1017879

Page: 3 of 3

Client: Vita Cellular Foams (UK) Limited

Conclusion

The foam meets the requirements of Schedule 1 Part 1 of the Furniture and Furnishings (Fire) (Safety) Regulations 1988 (as amended) S.I. No. 1324.

Where required to make a judgement to any pass/fail criteria an estimation of uncertainty of measurement has been taken into account. Under our Policy we have used a non-binary decision rule.

See our decision rules Policy (https://www.bttg.co.uk/about-us/decision-rules-policy/) for further information.

Uncertainty Budget

Timings: ±2 seconds.

Weights: ±2g.

Reported by:..... R Walls, Laboratory Technician

Countersigned by: B Bland, Technical Customer Service Officer

Enquiries concerning this report should be addressed to Customer Services.





1066